

A / Timber Doors

1- Hardware Set 1 / TD02- Apt. Entrance (Single / 1H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5790F/55 Niro	Mortise cylinder lock 55mm backset SSS square for end and strike, Fire Tested to DIN18250 90mn	T6-Wilka – Ger.	No.	1
3	1405/35x35 Mmv	Profile & turn cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel	T6-Wilka – Ger.	No.	1
4	CD55 Fisso / CD63 Cromat	ROBOTECH external fixed knob on plate with cylinder escutcheon	Colombo Design – Italy	Set	1
5	ID41 RY Cromat + ES	ROBOQUATTRO inside lever on round roses with cylinder escutcheons	Colombo Design – Italy	Set	0.5
6	Art. DSG1 SNP	SS finish door guard	ICSA – Italy	No.	1
7	Art. DV SNP	SS 200° door viewer with shutter	ICSA – Italy	No.	1
8	BOXER 2-4 GR	Integrated door closer for single doors, leaf depth from 40mm, according to EN1154A, size 2-4, up to 130KG leaf weight and up to 1100mm leaf width with arm & guide rail	Geze – Ger.	No.	1
9	HS-1250 FH+RD	Mortise automatic door bottom, UL tested, 48db Acoustical tested, UL listed for fire rating, 20mm drop down, 1250mm length	T6-Planet – Switzerland	No.	1
# Sets					see schedule

2- Hardware Set 2 / TD07- Bedroom, Kitchen & Maid's Room (Single / NFR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5790F/55 Niro	Mortise cylinder lock 55mm backset SSS square for end and strike, Fire Tested to DIN18250 90mn	T6-Wilka – Ger.	No.	1
3	1400/35x35 Mmv	Double profile cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel	T6-Wilka – Ger.	No.	1
4	ID41 RY Cromat	ROBOQUATTRO lever on round roses with cylinder escutcheons	Colombo Design – Italy	Set	1
5	Art. FDS10 SS	SS floor round door stopper	ICSA – Italy	No.	1
# Sets					see schedule

3- Hardware Set 3 / TD06- Bath & Toilet Doors (Single)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5725 (5125)/55 Niro	Mortise bathroom lock 55mm backset SSS square for end and strike to DIN18251 Class 3	T6-Wilka – Ger.	No.	1
3	ID41 RBZG Cromat	ROBOQUATTRO lever on round roses with bathroom roses	Colombo Design – Italy	Set	1
4	Art. FDS10 SS	SS floor round door stopper	ICSA – Italy	No.	1
5	MinE-V FH RD	Mortise automatic door bottom, UL tested, 23db Acoustical tested, ventilation compliant, 20mm drop down, 800mm length	T6-Planet – Switzerland	No.	1
# Sets					see schedule

4- Hardware Set 4 / TD02a, TD03 & TD04 - GSM Room, Storage, Electrical Room, Tel. Room & BMS (Single / 1.5H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-4353 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x89x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5790F/55 Niro	Mortise cylinder lock 55mm backset SSS square for end and strike, Fire Tested to DIN18250 90mn	T6-Wilka – Ger.	No.	1
3	1400/35x35 Mmv	Double profile cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel under Pat. MK made in Germany	T6-Wilka – Ger.	No.	1
4	R136 PZ SSS	RIVA 136 SS lever on roses with cylinder escutcheons tested to DIN1906 Class 4	T6-Dieckmann – Ger.	Set	1
5	TS2000 V-BC	Overhead door closer force 2-5 with regular arm bracket & back-check to EN1154 & Fire Tested to EN1634-1	Geze – Ger.	No.	1
# Sets					see schedule

5- Hardware Set 5 / TD01- Parking Entrance Door (Double / 1.5H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	8
2	Art. 4900 SSS	SS panic push bar 1157mm long to EN1125	T6-Wilka – Ger.	No.	2
3	Art. 6678/35 B Niro	Mortise anti-panic lock, change-over function B, integrated "plug-in key function" SS forend to EN1125 / Left hand	T6-Wilka – Ger.	No.	1
4	Art. 7664/35 Niro	Emergency exit lock case for automatic locking in inactive leaf	T6-Wilka – Ger.	No.	1
5	Art. 9647 (1m) / 9648 (1.5m)	Lower bolt 1m long with upper shooting bolt 1.5m long in massive steel material	T6-Wilka – Ger.	Set	1
6	Art. P645 / 9651 Niro	Upper and lower strike plates	T6-Wilka – Ger.	Set	1
7	Art. 4685 / 9653	Upper switching lock and lower shoot bolt guide	T6-Wilka – Ger.	Set	1
8	Art. 4910 / 4914 SSS	SS outside U shape lever on rose with cylinder escutcheon	T6-Wilka – Ger.	Set	1
9	1400/35x35 Mmv	Double profile cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel under Pat. MK made in Germany	T6-Wilka – Ger.	No.	1
10	Art. 4916/28-32-55	Split spindle	T6-Wilka – Ger.	No.	1
11	TS2000 V-BC-RA	Overhead door closer force 2-5 with reverse arm bracket & back-check to EN1154 & Fire Tested to EN1634-1	Geze – Ger.	No.	2
12	CH297D	Concealed door coordinator	Hager – U.S.A.	No.	1
13	HS-1250 FH+RD	Mortise automatic door bottom, UL tested, 48db Acoustical tested, UL listed for fire rating, 20mm drop down, 1250mm length	T6-Planet – Switzerland	No.	1
# Sets					see schedule

6- Hardware Set 6 / TD03a- Garbage Door (Single / 1.5H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-4353 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x89x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5791F/55 Niro	Mortise latch lock 55mm backset SSS square for end and strike, Fire Tested to DIN18250 90mn	T6-Wilka – Ger.	No.	1
3	R136 PZ SSS	RIVA 136 SS lever on roses with cylinder escutcheons tested to DIN1906 Class 4	T6-Dieckmann – Ger.	Set	1

4	TS2000 V-BC-RA	Overhead door closer force 2-5 with reverse arm bracket & back-check to EN1154 & Fire Tested to EN1634-1	Geze – Ger.	No.	1
# Sets					see schedule

7- Hardware Set 7 / TD05- Office Entry Door (Double / 1.5H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	8
2	5790F/55 Niro	Mortise cylinder lock 55mm backset SSS square for end and strike, Fire Tested to DIN18250 90mn	T6-Wilka – Ger.	No.	1
3	1405/35x35 Mmv	Profile & turn cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel	T6-Wilka – Ger.	No.	1
4	CD55 Fisso / CD63 Cromat	ROBOTECH external fixed knob on plate with cylinder escutcheon	Colombo Design – Italy	Set	1
5	ID41 RY Cromat + ES	ROBOQUATTRO inside lever on round roses with cylinder escutcheons	Colombo Design – Italy	Set	0.5
6	Art. 9224-0121-83	SS 21mm backset double action flush extension bolt for double doors	T6-Deni – Ger.	Set	1
7	Art. 5846-0001-83	SS dust excluding socket	T6-Deni – Ger.	No.	1
8	BOXER 2-4 GR	Integrated door closer for single doors, leaf depth from 40mm, according to EN1154A, size 2-4, up to 130KG leaf weight and up to 1100mm leaf width with arm & guide rail	Geze – Ger.	No.	1
9	HS-1250 FH+RD	Mortise automatic door bottom, UL tested, 48db Acoustical tested, UL listed for fire rating, 20mm drop down, 1250mm length	T6-Planet – Switzerland	No.	2
# Sets					see schedule

8- Hardware Set 8 / TD06a & TD09- Watchman & Male/Female Toilet (Single)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	5725 (5125)/55 Niro	Mortise bathroom lock 55mm backset SSS square for end and strike to DIN18251 Class 3	T6-Wilka – Ger.	No.	1
3	R136 PW SSS	RIVA 136 SS lever on roses with bathroom indicator roses tested to DIN1906 Class 4	T6-Dieckmann – Ger.	Set	1
4	Art. FDS10 SS	SS floor round door stopper	ICSA – Italy	No.	1
# Sets					see schedule

9- Hardware Set 9 / TD08- Staircase Door (Single / 1.5H FR)

	Code	Description	Brand	Unit	Qty.
1	Art. 970-433 SS	SS 2BB AISI304 hinge including pin, ball bearing, tip & screw, 102x76x3mm 120 Kg load capacity to EN1935:2002, 3H FR Certified UL	ICSA – Italy	No.	4
2	Art. 4900 SSS	SS panic push bar 1157mm long to EN1125	T6-Wilka – Ger.	No.	1
3	Art. 6678/35 B Niro	Mortise anti-panic lock, change-over function B, integrated "plug-in key function" SS forend to EN1125 / Left hand	T6-Wilka – Ger.	No.	1
4	Art. 4910 / 4914 SSS	SS outside U shape lever on rose with cylinder escutcheon	T6-Wilka – Ger.	Set	1
5	1400/35x35 Mmv	Double profile cylinder 5 anti-rust pins, anti-pick, 70mm long to DIN18252 EN1303 nickel under Pat. MK made in Germany	T6-Wilka – Ger.	No.	1

6	Art. 4916/28-32-55	Split spindle	T6-Wilka – Ger.	No.	1
7	TS2000 V-BC-RA	Overhead door closer force 2-5 with reverse arm bracket & back-check to EN1154 & Fire Tested to EN1634-1	Geze – Ger.	No.	2
8	HS-1250 FH+RD	Mortise automatic door bottom, UL tested, 48db Acoustical tested, UL listed for fire rating, 20mm drop down, 1250mm length	T6-Planet – Switzerland	No.	1
# Sets					see schedule